

Certificate of Analysis

Achilles Struktur Feinleinen LAM 125 μ

Description: Coated surface Polyester Polyethylene/Copolymer film, for use in encapsulation of printed materials as print finishing process. Adhesion is achieved by the reactivation of the heat sensitive resins in the Polyethylene/copolymer element.

Charakteristik: Fine linen structured surface

Construction: Base film: 75 micron polyester
Adhesive: 28 μ polyethylene + 22 μ EVA copolymer
Tolerance: +/- 5 %

Operation temperature: 135°C – 140°C at speed of 650 mm/min

Properties		Unit	Test-Method	Typical Values
Thickness		μm	ISO 4593/DIN 53370	125 (tolerance 2%)
Tensile Strength	MD	MPa	DIN EN ISO 527	46,5
	TD			52,0
Elongation at break	MD	%	DIN EN ISO 527	144
	TD			119
Coefficient of friction	m/m	–	DIN EN ISO 8295	0,32
Heat Shrinkage	MD	%	DIN 53377	– 0,4
	TD			– 0,7

MD = machine direction
TD = cross machine direction

The details contained in this bulletin comply with the current state of our know-how; they do not constitute any extension of the guaranteed services stipulated in our delivery conditions and are in particular no warranted properties. This information bulletin can only provide unbinding advice with regard to differences in printing substrates and working conditions. Before circulation printing begins, it is important for the printers to check by suitable means whether the materials are appropriate for the intended purpose.